



DELTAPLUS

YOUR SAFETY AT WORK






SAFETY HELMETS



HOW TO CHOOSE YOUR HELMET ?



		ESSENTIAL			
		ZIRCON I	QUARTZ I	QUARTZ UP III	
EN397	Compulsory	<ul style="list-style-type: none"> • Impact* : Energy spread to the head form must not exceed 5 kN after the fall of an object of 5 kg at 1m high • Penetration* : the tip of the test mass used (3 kg 1 m) must not come into contact with the skull • Flammability : the helmet must not burn with flame emission more than 5 s after removal of the flame <p>* Testing impact and penetration is made at room temperature, at +50 °C and at -10 °C</p>	<p>Material : HDPE Weight : 370 g Harness : LDPE Visor : Normal</p> <p>Electrical works</p> 	<p>Material : Polypropylen Weight : 346 g Harness : LDPE Visor : Normal Ventilated</p> 	<p>Material : Polypropylene Weight : 322 g Harness : Textile Visor : Normal</p> <p>Electrical works</p> 
		<p>+150°C In extreme temperatures: testing impact and penetration are made at room temperature at +150 °C, at -20°C or -30 °C</p> <p>-20°C</p> <p>-30°C</p>	<p>+50°C ↓ -10°C</p>	<p>+50°C ↓ -10°C</p>	<p>+50°C ↓ -30°C</p>
		<p>440VAC Protects against accidental contact with a short conductor electrical voltage up to 440 V</p>	<p>440 VAC</p>		<p>440 VAC</p>
		<p>LD Protects against lateral compression. The maximum deformation of the helmet should be ≤40 mm</p> <p>MM Resistance to splashes of molten metal</p>			<p>MM</p>
EN50365	Compulsory	<p>Electrically insulating helmets for use on or near live installations not exceeding 1000 VAC or 1500 VDC.</p>			

> Identification of the manufacturer
> Size Range

DELTA PLUS
53 - 63 cm

CE marking
> Standard no
> Model name of the helmet
> Optional requirements
> EN50365 standard
> Batch no

CE EN397:1995
A1:2000
DIAMOND V
-30°C **LD MM 440VAC**
▲ **Classe 0**
Batch NR :
production date



ZIRCON - QUARTZ I




SUPER QUARTZ - DIAMOND



QUARTZ UP III - QUARTZ UP IV
GRANITE

Year and month of manufacture :
Helmet lifespans :
ZIRCON QUARTZ UP :
 5 years from date of manufacture,
 3 years in use.
SUPER QUARTZ, DIAMOND, GRANITE :
 7 years from the date of manufacture,
 4 years in use.





EVOLUTION		PREMIUM			
QUARTZ UP IV	SUPER QUARTZ	BASEBALL DIAMOND V	BASEBALL DIAMOND UP	GRANITE PEAK	GRANITE WIND
Material : Polypropylene Weight : 322 g Harness : Textile Visor : Normal Ventilated	Material : ABS / Polycarbonate Weight : 410 g Harness : Textile Visor : Normal <i>Heavy industry Iron and steel industry +150°C</i>	Material : ABS Weight : 368 g Harness : Textile Curved visor <i>Electrical Works</i>	Material : ABS Weight : 368 g Harness : Textile Curved visor Removable chin strap with 3 points of fixing <i>Electrical Works Work at height</i>	Material : ABS Weight : 350 g Harness : Textile No visor Removable chin strap with 3 points of fixing <i>Electrical Works Work at height</i>	Material : ABS Weight : 355 g Harness : Textile No visor Removable chin strap with 3 points of fixing Ventilated <i>Work at height</i>
+50°C ↓ -30°C	+150°C ↓ -30°C	+50°C ↓ -30°C	+50°C ↓ -30°C	+50°C ↓ -20°C	+50°C ↓ -20°C
	440 VAC	440 VAC	440 VAC	440 VAC	
	-LD-	-LD-	-LD-		
MM	MM	MM	MM	MM	MM

SNR 32
MAGNY HELMET

SNR 27
SUZUKA

WINTER CAP

FUEGO

BASALPHA
BASGAMMA

HARNES V

Spare harness for
BASEBALL DIAMOND V

KIT MINES (on request)

VISOR HOLDER
VISOR TORIC - VISORPC - VISORG

ZIRCON - QUARTZ - DIAMOND

BADGE HOLDER

Europe : 40 pcs
China : 320 pcs

VISOR HOLD MINI
VISORGINI
VISORPC MINI

GRANITE

2 pts

JUGALPHA
MENTALPHA

4 pts

DYNAMIC JUGALPHA

ZIRCON - QUARTZ - DIAMOND

3 pts

JUGAMMA

GRANITE WIND
GRANITE PEAK

30 mm

NEW SERVICE FROM DELTA PLUS: CUSTOMIZE YOUR SAFETY HELMETS!

- > The logo sent must be in vectorized format (.eps, .ai, or .pdf) and do not have different colour background of the chosen helmet.
- > For logos in colours, thanks to give us the pantone reference for each colour.
- > Warning: the colours of the logos can be slightly changed according to the colour of helmets. To have the same colour as your logo, we recommend to choose white helmets.
- > It is impossible to do gradient colours in pad printing.
- > Minimum of order :
40 pieces per colour for all orders in Europe
- > Maximum number of colours: 4
- > The space to put the logo may not exceed dimensions shown on the schema below :



ZIRCON	QUARTZ - SUPER QUARTZ	GRANITE	BASEBALL DIAMOND
<p>70 YOURLOGO 40</p> <p>Front</p>	<p>70 YOURLOGO 40</p> <p>Front</p>	<p>70 YOURLOGO 40</p> <p>Front</p> <p>Notice: only front printing available</p>	<p>70 YOURLOGO 40</p> <p>Front</p>
<p>60 YOURLOGO 20</p> <p>Back</p>	<p>60 YOURLOGO 35</p> <p>Back</p>		<p>60 YOURLOGO 20</p> <p>Back</p>

Sizes mm

PRICELIST AND SALES TERMS

